

Door & frame sets

Data sheet E4

Application	For use in Diagnostic departments such as X-Ray, CT and PET Scanner rooms to shield against the harmful effects of radiation.
Description	<p>A Lead-lined timber door and frame set.</p> <p>The doors are pre-hung on bearing hinges and each frame set includes two sets of architrave, one of which is lead lined.</p> <p>Where ever possible the lead is completely concealed from view.</p> <p>Fire rated doors are available in both half hour and one hour options.</p>
Finish	Most timber finishes are available. Hardwoods are generally sealed to receive top coats on site by others. Paint finish door sets are supplied primed only.
Dimensions	<p>The standard frame depth is 130mm. Other depths are available on request.</p> <p>Generally, widths and heights are made to suit individual contracts.</p>
Shielding	Available in Lead-equivalents: 0.5mm to 5mm in increments of 0.5mm
Installation	Fitting can be undertaken by a competent craftsman. Attention should be paid to using the correct fixings when installing heavy products. Envirotect offer a fitting service if required.
Accessories	<ul style="list-style-type: none">- Fitting of specified or free issue ironmongery- Vision panels- Laminate or Acrovyn facings
Availability	All door & frame sets are manufactured to customer's specification. Please phone for a current delivery period.
Contacts	Envirotect Ltd Tel 01525 374374 Fax 01525 219786 e-mail info@envirotectltd.co.uk Web www.envirotectltd.co.uk